



$R1 = 0.003$  p.u. and  $X1 = 0.00055$  p.u. for 100KVA base.

### Load

Plant load includes the welding machine which contributes to the majority of the load, wire drawline machine and existing multi-step 1680 KVAR, SCR switched PF correction unit.

### Welding Machine

#### Summary

The welding machine utilises nine welding transformers. Each three transformers are dedicated for one phase. The primary of each transformer is individually controlled by SCR controllers fed from the welding machine's control system.

#### Profile of the welding signal

A single welding action consists of ramp up period in 10 ms increments, then a hold period in 10 ms intervals where maximum current is achieved then a similar ramp down. Depending on the product line the ramp, hold time and load current will vary. In some product lines, a single weld can go up to 250ms with repetition every second for 52 seconds. The plant can produce welded mesh for 6 main diameters, with each diameter having a unique length and width.

#### Preliminary site measurements

For each product line with the PF controller in automatic mode, data were captured from site which included measurements for voltage, current, voltage-drop, KW, KVAR and KVA for single and complete welding cycle. Flicker indices were recorded using a flicker meter. The measurements were also repeated with PF controller disabled.

#### Preliminary analysis

Data was used to derive a model for the welder for each product line. The model was derived using ATP software. Simulation results were compared with site measurements to verify the accuracy of the model. Flicker indices were also evaluated from the simulated voltage waveforms using methods addressed in IEC 61000-3-7 then compared with site measurements. In order to achieve maximum accuracy, flicker indices were evaluated using method 1;  $PST = 1$  curve for rectangular voltage changes [1]. The results were also confirmed from method 2; simplified assessment procedure for aperiodic voltage changes [1]. Measurements taken with PFC OFF indicated the presence of significant voltage drop during a single weld. Careful analysis of KVAR, KW and KVA measurements showed that the voltage drop is due to real and reactive power. Voltage drop contributed from the reactive power is around 66% of the total voltage drop. Similar values of voltage drop were recorded with PFC ON. This had a strong indication that the PFC controller was not regulating PF during a welding cycle. In Figure 2, the voltage drop is substantial during a single weld which is consistent with the PFC controller not engaging enough steps to regulate the PF. After the weld cycle ends (load current drops), the PFC controller could

not responded to load changes and capacitor steps were still engaged for 40ms causing a voltage rise. This voltage rise made the flicker values worse when compared with measurements while PFC was turned OFF. This trend is common across all product lines.




Figure 2: Bus voltage during a single weld with PFC ON

### Secondary test

#### Aim:

- Determine the response time of the PFC controller.
- Identify electrical system's response with PFC equipment forced ON during a weld cycle.
- Identify system's voltage drop at unity PF.

#### Description:

- Demonstrate system's voltage drop during a weld whilst PFC controller is forced ON.
- Record several measurements for voltage drop, PF, KVA, KW and KVAR.
- Eliminate the effect of PFC controller's response time on measurements.

#### Methodology:

- Manually engage capacitor banks in steps until 970 KVAR is achieved.
- Monitor system's voltage to reduce the risk of overvoltage trips.
- Apply several measurements for voltage drop, PF, KVA, KW and KVAR.
- Repeat the above test with PFC controller set to Automatic mode.

#### Analysis:

- Measurements applied with PFC in Automatic mode showed a voltage drop of 39.67V during single weld with system voltage of 425V.

- Recorded KVA, KW and KVAR are 1500, 1000, 1000 respectively.
- Measurements applied with PFC forced ON showed a voltage drop of 15 V during single weld when referred to system voltage of 425V (figure 4).
- Recorded KVA, KW and KVAR are 1028, 1000, 220 respectively.
- Voltage drop is mainly contributed to real power.




Figure 3: Voltage drop with PFC in Automatic mode




Figure 4: Voltage drop with PFC controller forced ON

**Proposed solution**

HVC will regulate system’s reactive current during welding cycles. HVC will utilize AccuSine® Power Correction System (PCS) operating in EVC mode and existing PFC system (Figure 5).

**PFC system:**

- PFC will be fixed on the electrical system to support load without any delay.
- Logic system will be implemented to switch ON the steps in sequence prior to production. The steps maybe forced ON manually as an alternative.
- Logic system will be implemented to switch OFF the steps in sequence when production has ended.

**AHF EVC:**

- AHF will remain powered up and activated (in run mode) at all times.
- As load demand varies, AHF will adjust its output to maintain the mains reactive current equal to nil within the accuracy of the measuring CTs.




Figure 5: HVC layout utilising AccuSine® EVC &PFC

## F82 sample results

### HVC system OFF:

- Calculated  $P_{st}$  levels from simulation at the low voltage bus using methods 1 & 2 are 12.77 & 11.47 respectively.
- Levels of  $P_{st}$  measured at the low voltage bus are 12.5.
- Calculated  $P_{st}$  levels from simulation at 22KV bus using methods 1 & 2 are 1.1 & 0.98 respectively.
- Levels of  $P_{st}$  measured at 22KV bus are 1.2.

### HVC system ON:

- Calculated  $P_{st}$  levels from simulation at the low voltage bus using methods 1 & 2 are 4.1 & 4.45 respectively.
- Calculated  $P_{st}$  levels from simulation at 22KV bus using methods 1 & 2 are 0.351 & 0.38 respectively.
- Figure 6 shows a decrease in system's voltage drop ( $\Delta V$ ) across the supply's impedance from 40-volts to near 20-volts when supply's reactive current is nil.




Figure 6: Simulated system  $\Delta V$  when HVC is ON "PFC OFF"

## METHOD TO MODEL ACCUSINE® (PCS) FOR HVC OPERATION

The method proposed will aid users to simulate the effect of HVC on  $\Delta V$  during welding cycles. The model was prepared using ATP software. The process requires cycle by cycle measurements for KW & KVAR for each product profile. In this paper the mesh welder will be modeled as a resistor in parallel with an inductor. A specific model will have to be prepared for each product profile. HVC will be modeled as a current source in parallel with existing PFC. A key factor in deriving the model is the addition of delay in the response of the current source. This will provide accurate representation of  $\Delta V$  during a welding cycle. As a simple approach, the user may incorporate a delay function

in the current source model. To allow for worst case scenario, HVC system has been modeled with an inherit delay response of 20ms. Consequently, the supply will support the load for a period not exceeding 20ms. Effect of HVC delay is shown in (Figure 6). For almost 20 ms,  $\Delta V$  is maintained at 40-volts, then HVC becomes active and the voltage drop declines to near 17-volts. Main advantage of using the existing PFC system is to allow the AccuSine® Power Correction System (PCS) to charge its dc bus without incurring any voltage drops during welding cycles. Figure 7 shows  $\Delta V$  during a welding cycle with PFC permanently turned ON. In this case, the PFC will support the load at all times with AccuSine® Power Correction System (PCS) maintaining PF at unity. The system response is enhanced, due to  $\Delta V$  being kept low throughout the welding cycle. After the weld cycle is finished, AccuSine® will correct for the leading current from PFC. In (Figure 7),  $\Delta V$  is maintained to near 17-volts throughout the welding cycle. After the cycle ends, AccuSine® is correcting leading PF from the permanently switched PFC for 3 cycles. AccuSine® will then need to charge its dc bus thus seizing its output for 20ms. During this period,  $\Delta V$  across the supply internal impedance will rise to 40-volts. It is important to note that the bus will be capacitive.




Figure 7: Simulated system  $\Delta V$  when HVC is ON "PFC ON"

## Conclusion

HVC can be utilized as a reliable solution for flicker mitigation. A simple guideline has been presented to help users model AccuSine® Power Correction System (PCS) to operate as HVC. A sample case has been documented with detailed analytical procedure and simulation results. Modeling & simulation was prepared using ATP software.

## REFERENCES

- [1] Assessment of emission limits for the connection of fluctuating load installations to MV, HV and EHV power systems, IEC61000-3-7:2007, ED.2/DTR.