



Frankfurt (Germany), 6-9 June 2011

**A BALANCED SCORECARD APPROACH
FOR THE ENHANCEMENT OF
DISTRIBUTED RENEWABLE PENETRATION
LIMIT IN ISOLATED NETWORKS**

Presented by: Dr. Worawit Tayati



Frankfurt (Germany), 6-9 June 2011

Outlines

- Introduction
- Problem definition
- Methodology
- Study results
- Conclusions
- Discussion



Frankfurt (Germany), 6-9 June 2011

Horizon Power – Who are we?



- ❑ Vertically integrated
- ❑ State owned
- ❑ Service regional towns and remote communities
- ❑ 2.3 Million sq.km
- ❑ 43,000 customers
- ❑ Excluding the South West Interconnected System (SWIS) ~ 700,000 cust.



Frankfurt (Germany), 6-9 June 2011

Our service area



- ❑ 30 isolated systems (~0.2 – 30MW)
- ❑ The North West Interconnected System NWIS (~500MW)
- ❑ Fuel mix – Gas, diesel
- ❑ Hydro - North East
- ❑ Wind - coastal
- ❑ Solar PV – inland
- ❑ Controlled and centralised RE systems



Frankfurt (Germany), 6-9 June 2011

PV/Diesel/Flywheel hybrid system




W.Tayati and G.Pack – Australia – Session 4 – Paper ID 0928





Frankfurt (Germany), 6-9 June 2011

Integration of Wind - Esperance



W.Tayati and G.Pack – Australia – Session 4 – Paper ID 0928






Frankfurt (Germany), 6-9 June 2011

LARGE TOWN (ESPERANCE)


- 33kV Network
- ~ 22MW peak demand
- 7x 5MW Gas turbine
- ~ 2500 HV cct.kms





Frankfurt (Germany), 6-9 June 2011

Our Strategy Wheel



- ❑ Cost of energy
 - 0.23 - 1.68 \$/kWh
- ❑ GHG Emission
 - 0.68 kgCO₂e/kWh
- ❑ Reliability (/yr/cust.)
 - SAIFI -2.43 (6.6*)
 - SAIDI-162 (290*min)

*Target



Frankfurt (Germany), 6-9 June 2011

Outlines

- Introduction
- Problem definition
- Methodology
- Case study results
- Conclusions
- Discussion



Frankfurt (Germany), 6-9 June 2011

Problem & Drivers

Drastic increase in PV installations
exceeding current limits

- Abundant solar resources
- Decreasing PV panel cost
- Generous Government Incentives
 - RECs - capital cost subsidy
 - FiTs (40c/kWh) - net feed-in



Frankfurt (Germany), 6-9 June 2011

Technical Issues

- System reliability concern
 - Small, isolated systems
 - Low fault level, low inertia
 - No other sources of supply
 - Extensive HV overhead networks

- LV / MV voltage rise issue
 - Evidence of customer PV inverters trip off
 - LV network operating voltage sets too high



Frankfurt (Germany), 6-9 June 2011

Outlines

- Introduction
- Problem definition
- Methodology
- Case study results
- Conclusions
- Discussion



Frankfurt (Germany), 6-9 June 2011

Methodology

- ❑ Reviewing existing penetration limit
 - Stability and network design
- ❑ Identifying enhancement strategies
 - Power station and network
- ❑ Assessing - balanced scorecard
 - Strategy wheel, technical, commercial aspects
- ❑ Validating – a case study



Frankfurt (Germany), 6-9 June 2011

Existing limits

Supply Quality = PQ + Reliability

- Power station (P/S) limit : reliability
 - Step load < unit rating (N+1 spinning reserve)
 - Stand alone = no other sources of supply

- Network limit : power quality (PQ)
 - LV PV < 20% of Tx rating – islanding
 - LV/MV voltage rise



Frankfurt (Germany), 6-9 June 2011

Rule of Thumb

PV limit is the minimum of the followings:

- ❑ 50% smallest generating unit
- ❑ 15% of peak demand – diesel generation
- ❑ 10% of peak demand – gas generation

And :

- ❑ De-rating of PV output due to temperature and inverter efficiency by ~70%




Frankfurt (Germany), 6-9 June 2011

Enhancement strategies

- ❑ Power quality (PQ)
 - Network reinforcement (NR)
 - PV inverter sophistication - output curtailment
- ❑ Reliability
 - Under Frequency Roll Off (UFRO)
 - Extra spinning reserve (Ex SR) + PV forecast
 - PV Fault Ride Through (FRT)
 - Distributed UFLS - demand response
 - Energy Storage (ES) & AMI

A Balanced Scorecard (BSC)

- ❑ Economics
- ❑ Environmental
- ❑ Social - Customer equity
- ❑ Technical
 - Effectiveness
 - Uptake
- ❑ Commercial
 - IPP contracts < 10% RE





Frankfurt (Germany), 6-9 June 2011

CASE STUDY - Carnarvon

Selection Criterion:

- ❑ PV penetration exceeding current limits
- ❑ Horizon Power owned P/S
- ❑ New P/S under construction
 - Opportunity to implement innovative enhancement strategies
- ❑ Centralised wind energy integration envisaged




Frankfurt (Germany), 6-9 June 2011

Outlines

- Introduction
- Problem definition
- Methodology
- Analysis of results
- Conclusions
- Discussion

Network Fault Studies

Impact of network faults on distributed PV





Frankfurt (Germany), 6-9 June 2011

Network Fault Studies

- ❑ Faults near to P/S, voltage depression
- ❑ Faults away from P/S, system frequency dips (due to high R/X ratio)
- ❑ PV inverters may trip on UV or UF

“Adverse impacts on power station stability”



Frankfurt (Germany), 6-9 June 2011


PV Fault Ride Through

- ❑ Investigate effects on PV of network faults followed by feeders trip and reclose
- ❑ Determine effectiveness of PV FRT functionality



Frankfurt (Germany), 6-9 June 2011

“PV FRT enhances system reliability”





Frankfurt (Germany), 6-9 June 2011

BSC for Carnarvon

BALANCED SCORECARD		NR	UFRO	FRT	UFLS	ES	AMI	Ex SR
		1	2	3	4	5	6	7
ECONOMIC	COST	Good	Fair	Good	Fair	Bad	Bad	Fair
ENVIRONMENTAL	EMISSION	Good	Good	Good	Good	Good	Good	Bad
SOCIAL	EQUITY	Good	Good	Good	Good	Good	Fair	Good
	ACCEPTABLE	Good	Good	Good	Bad	Good	Good	Good
TECHNICAL	EFFECTIVE	Good	Good	Good	Bad	Good	Fair	Good
	UPTAKE	Good	Good	Bad	Fair	Good	Bad	Good
COMMERCIAL	IPP CONTRACT	Good	Good	Good	Good	Fair	Good	Bad
OPERATION	SIMPLICITY	Good	Good	Fair	Good	Fair	Good	Bad
Legend:		Good	Fair	Poor	Bad			




Frankfurt (Germany), 6-9 June 2011

Summary – Case Study

- ❑ Network Reinforcement (NR) recommended
- ❑ UFRO recommended for new P/S
- ❑ PV FRT considered, improve reliability
 - ❑ Proven technology, uptake?
- ❑ UFLS – uptake?, effectiveness?
- ❑ Energy storage – cost barrier
- ❑ AMI – uptake?, cost
- ❑ Extra SR – commercial contract, more emission, cost

Spinning reserve


(Based on N+1 operating philosophy)



Loss of Total PV

Loss of Single Unit

Possibility of Higher PV Penetration



Loss of
Single
Unit

Loss of
Total PV



Frankfurt (Germany), 6-9 June 2011

Outlines

- Introduction
- Problem definition
- Methodology
- Study results
- **Conclusions**
- Discussion



Frankfurt (Germany), 6-9 June 2011

Conclusions

- ❑ Small power system supply quality is susceptible to level of distributed PV penetration
- ❑ Expectation to accommodate distributed PV
- ❑ Our deterministic limits based on spinning reserve may be too conservative
- ❑ There are opportunities to increase decentralised PV penetration limits using a risk based probabilistic approach e.g.
 - ❑ Probability of not all PV disconnecting following faults
 - ❑ Probability of fault frequency (fault rate)
 - ❑ Probability of PV output not at installed capacity (temperature, cloud cover, incident angle, etc.)



Frankfurt (Germany), 6-9 June 2011

Outlines

- Introduction
- Problem definition
- Methodology
- Study results
- Conclusions
- Discussion



Frankfurt (Germany), 6-9 June 2011

**THANK YOU FOR YOUR
ATTENTION
QUESTIONS?**